



# 3 Ton High Wall Fan Coil (24v Control)

## Fan Coil Pared Alta de 3 Toneladas (Control 24v)

**Models / Modelos**  
**MUWNT-36**

**230 V**



### Technical Specifications / Especificaciones Técnicas


\*Comes with step-down transformer\*

Model		MUWNT-36	
Power supply		V-Ph-Hz	230-1-60
Cooling	Capacity	Btu/h	36000
	Input	W	3210
	Rated current	A	14.5
	EER	W/W	2.74
Max. input consumption		W	4350
Max. current		A	20
Starting current		A	71
Indoor fan motor	Model		RPG60B
	Input	W	113
	Capacitor	uF	3.5
	Speed (Hi/Mi/Lo)	r/min	1210/1080/900
Indoor coil	Number of rows		2
	Tube pitch x row pitch	mm	21 x 13.37
	Fin spacing	mm	1.2
	Fin type (code)		Hydrophilic aluminium
	Tube outside dia. and type	mm	Φ7,inner grooved tube
	Coil length x height x width	mm	965 x 420 x 26.74
	Number of circuits		5
Indoor air flow (Hi/Mi/Lo)		m <sup>3</sup> /h	1360 / 1190 / 950
Indoor noise level (Hi/Mi/Lo)		dB(A)	52 / 47 / 42
Indoor unit	Dimension (W*D*H)	mm	1259 x 282 x 362
	Packing (W*D*H)	mm	1340 x 450 x 380
	Net / Gross weight	Kg	19.4 / 25.2

### Features and Benefits



Manual Switch Button



High Density Filter



Mute Operation



Anti-cold Air Function



2-Way Draining Connection



Refrigerant Leakage Detect



Emergency Using Function